

Product Data Sheet: ASPHALT PAINT

5L



AVAILABLE COLOURS

A WATER BASED ACRYLIC FORMULATION, DEVELOPED FOR PAINTING ASPHALT, BITUMEN AND TARMAC SURFACES.

FixMaster Asphalt Paint is suitable for a wide variety of surfaces including bare concrete, asphalt, wood and previously painted floors.

- Excellent resistance to UV and weathering
- Suitable for light/medium trafficked areas
- Roller, brush or spray application
- Suitable for internal and external areas
- Acrylic resin
- No mixing required

HOW TO USE IT:

Surface Preparation

Ensure surfaces are clean, dry as possible and free from any loose material. Remove any dirt, oil, surface laitance or grease.

Mixing

Mix thoroughly using a wide bladed stirrer.

Application

Apply by brush, long pile roller or spray. Do not flood and spread apply. Best results are obtained in warm (minimum 15°C) conditions with a good through draught. For Asphalt surfaces work the product into all voids around the aggregate but avoid pooling of the paint in such voids. On bare concrete floors it is recommended that the first coat is diluted with up to 20% water by volume prior to application. This will help to seal the surface. Once dried, a second coat can be applied at full strength.

Not recommended for concrete where vehicles will be parked. On previously painted surfaces it is recommended to apply two thin coats rather than one thick coat. This will prolong the life and performance of the coating.

CURING TIMES @ 15-20°C:

Touch Dry	1 hour
Foot Traffic	12 hours
Wheeled Traffic	24 hours

COVERAGE:

5L will cover approximately 30m². Coverage will be reduced on porous or open textured surfaces.

SHELF LIFE:

One year in sealed containers. Store in a cool dry and well-ventilated place. (5-30°C)

CLEANING TOOLS:

Use clean cold water.

MAINTENANCE:

Remove dirt with a soft broom or light scrubbing machine. Do not steam clean or subject to temperatures above 60°C.

SAFETY:

Refer to the Material Safety Data Sheet for information on correct handling and application of the product.