


Product Data Sheet: EPOXY PAINT WB ANTI SLIP

5L



AVAILABLE COLOURS

A HARD WEARING AND FINELY TEXTURED ANTI-SLIP COATING FOR ADDED SAFETY IN HEAVY WEAR AREAS

FixMaster Epoxy Paint WB Anti-Slip is a water based, solvent free epoxy resin coating system with pre-dispersed lightweight aggregates providing a hard-wearing durable surface. The fine textured finish is both attractive and easier to keep clean.

- Resistant to oils, solvents and most harsh cleaning chemicals
- User friendly – Solvent Free & Low Odour
- Will not attack existing coatings
- Suitable for forklift traffic
- Common areas of use include garages, cellars, factories, walkways and food processing areas

Surface Preparation

New concrete must be at least 4 weeks old. Surfaces should be clean and dry. Smooth or new concrete will require either mechanical abrasion or treated with an acid etch cleaner. Grease, oil and other contamination should be cleaned using a degreaser. Can be applied over existing coatings but they must be well bonded and lightly abraded. Wooden surfaces will require abrading to remove dirt. Two or three coats may be required on porous surfaces. Not recommended for use on metal or most latex levelling compounds.

Mixing

Supplied in pre-weighed units and should be mixed in full. Stir both components separately before mixing together thoroughly with 1L of clean water. Mix by drill with a suitable mixing attachment working around the sides and base to ensure all of the liquid is mixed and the aggregate is evenly dispersed. Mix continuously for 3-5 mins until a uniform colour and consistency is achieved. Decant into a shallow tray ready for application.

Application

One coat will act as a priming and sealing coat. The second coat will provide a uniform and attractive finish and can be applied as soon as the first coat is dry. Application is best in a temperature between 15-25°C with a medium pile simulated sheepskin roller. Re-stir the paint at regular intervals to ensure even distribution of the aggregate. Do not apply to a floor temperature below 5°C and avoid washing the floor for 7 days.

CURING TIMES @ 15°C:

Foot traffic 24-36 hours

COVERAGE:

5-6m² per KG, per coat (2 coats recommended). Coverage will be reduced on porous surfaces, open textured surfaces.

POT LIFE @ 15°C:

45-60 minutes

SHELF LIFE & STORAGE:

One year in sealed containers, do not allow to freeze.

CLEANING TOOLS:

Tools can be cleaned with warm soapy water, although part cured product on rollers will be difficult to remove and may need to be disposed of.

MAINTENANCE:

Remove dirt with a soft broom or light scrubbing machine. Do not steam clean or subject to temperatures above 60°C.

SAFETY:

Care should be taken to avoid skin and eye contact. Wear gloves and protective clothing. Harmful if taken internally. Guard against naked flames and smoking. Material Safety Data Sheets available upon request.