

## Product Data Sheet:

RoofProof

Waterproofs Roofs Instantly

5kg

Dark grey

### **AN ACRYLIC, SOLVENT-BASED COATING WITH REINFORCING FIBRES WHICH CAN BE APPLIED AS A HIGH BUILD OR STANDARD COAT.**

FixMaster RoofProof provides an effective all-weather treatment for the remedial repair of leaking roofs and gutters. It can even be applied in the rain in emergencies. When cured it produces a flexible and impervious membrane. Excellent adhesion to a wide range of building materials including asphalt, bitumen, concrete, brickwork, slates, metals and felt.

- Damp weather emergency application
- Fibre reinforced
- Excellent adhesion and flexibility
- Single coat application
- Ready to use - no mixing required
- Solvent-based
- Repairs splits and cracks in roofs

### **HOW TO USE IT:**

#### **Surface Preparation**

Ensure surfaces are free from loose dirt, oil & grease contamination, stone chippings, lichen, moss and standing water. RoofProof can be applied in the rain, but optimal performance is achieved in good conditions to a dry surface. Fungicidal growth should be removed with a suitable wash. Metal surfaces should be wire brushed to remove scale or rust.

#### **Limitations**

Do not use on Styrofoam or PVC foil or in areas where solvent or oil contact is likely. Not recommended for internal use, wood, tanking, fishponds and balconies. Air conditioning units should be sealed during application and 48 hours afterwards. Not Suitable for heavy foot traffic.

### **Application**

Apply by roller or brush at 1-2mm ensuring an even coverage free from pinholes. RoofProof will fill and bridge gaps up to 3mm. If wider cracks are present, cover with a suitable flexible scrim bedded into the coating. If the surface is damp, work the product into the surface to disperse excess moisture and ensure a good bond. Apply between 5-25°C.

### **DRYING TIME:**

Generally, 48-72 hours, but can take up to 7 days depending on temperature and humidity. The product may remain soft for a further period, this is not detrimental to the waterproofing qualities.

### **COVERAGE:**

High Build 2kg per m<sup>2</sup>- Standard 1kg per m<sup>2</sup>.

### **SHELF LIFE:**

Up to 2 years in sealed containers stored in a cool, dry place away from sources of ignition or naked flame.

### **CLEANING TOOLS:**

Clean immediately with a solvent based cleaner.

### **SAFETY:**

RoofProof is a solvent-based product and therefore care should be taken to avoid contact with eyes and skin. Ensure adequate ventilation and do not smoke when using the product. The product and container must be disposed of as hazardous waste. Material Safety Data Sheets available upon request.